

MASCAR

Technical data	UM	MULTIWRAP 130	
Baler			
Chamber	type	Fixed	
Bale diameter	cm	130	
Bale width	cm	120	
Rollers number	n.	18	
Total pickup width	cm	210	
Pickup width (DIN 11220)	cm	200	
Bars tine/each bar	n.	4/28	
Tine pitch	mm	65	
Cutting system CUT – CUT.25	n.	15 (0-7-15)	
Cutting lenght	mm	70	
Automatic knives cleaning		Standard	
Drop floor		Standard	
Net binding		Standard	
Double twine binding		Optional	
Automatic chains lubrication		Standard	
Centralized greasing system		Standard	
Semi-automatic greasing		Optional	
Electric greasing		Optional	
Bale compression plates		Standard	
Tires		600/55-22.5	
Pneumatic braking system		Optional	
EU approval		Optional	
Electric supply		12 V – 25 A	
Led lighting system		Standard	
Hydraulic tractor requirements		1 x single acting + free return	
Drawbar		Adjustable	
Cardan shaft		Homokinetic with automatic torque limited (2100 Nm)	
Min. power requirements	kW (hp)	88 (120)	
P.T.O.	RPM	540	
7" color graphic terminal		Standard	
Bale wrapper			
Automatic work cycle		Standard	
Film reel height	mm	750	
Film break detection		Standard	
Single film wrapping mode		Standard	
Vertical bale overturning kit		Optional	
Dimensions			
Width	cm	294	
Height	cm	267	
Length	cm	630	
Empty weight	kg	4860	4920